

Deckshield IDSD High Grade

A solvent free, flexible polyurethane ramp coating system that is finished with bauxite/emery aggregates for a highly textured, antislip finish.

Provides a suitable surface for steep and circular internal car park ramps.



Excellent Slip Resistance:

Highly textured finish to provide a safe environment for vehicular ramp users.



Fire Resistant:

Provides a safe environment for car parking facilities.



Hard-Wearing:

Hard-wearing & abrasion resistant suitable for regular vehicle traffic.



Solvent Free:

Solvent free, low in VOCs and environmentally friendly.



Technical Profile*

FIRE RESISTANCE			
EN 13501-1	B ₁ - s1		
SLIP RESISTANCE**			
Method described in BS 7976-2 (typical values for 4-S rubber slider)	Dry > 40, Wet depends on specification (in accordance with HSE and UKSRG guidelines)		
THERMAL RESISTANCE			
Softens over 70°C, Hardens on cooling			
ABRASION RESISTANCE			
Taber Abrader (1 kg load using H-22 wheels)	50mg loss per 1000 cycles		
WATER PERMEABILITY			
Nil - Karsten test (impermeable)			
BOND STRENGTH			
Greater than cohesive strength of 25 N/mm ² concrete. > 1.5 MPa			
SPEED OF CURE	10 °C	20 °C	30 °C
Light Traffic	30 h	16 h	10 h
Full Traffic	36 h	24 h	16 h
Full Chemical Cure	12 d	7 d	6 d

* These figures are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.


**The slipperiness of flooring materials can change significantly, due to the installation process, after short periods of use, due to inappropriate maintenance, longer-term wear and/or surface contaminants (wet or dry). Textured systems are recommended to meet slip resistance value requirements for wet conditions and/or surface contaminants (wet or dry) - please contact our Technical Advisors for further details and specifications.

Model Specification

System	Deckshield IDSD High Grade
Finish	Highly Textured
Thickness	Dependant on specification
Manufacturer	Flowcrete Asia

Preparatory work and application in accordance with manufacturer's instructions.

System Design



Products Included In This System

Primer	Flowprime
Sand Scatter	Natural Quartz
Basecoat	Deckshield SF (Black)
Finishing	Bauxite/Emery Aggregates

Detailed application instructions are available upon request.

Substrate Requirements

Concrete or screed substrate should be a minimum of 25 N/mm², free from laitance, dust and other contamination. Substrate should be dry to 75% RH as per BS8204 and free from rising damp and ground water pressure.

Installation Service

The installation should be carried out by a licensed contractor with a documented quality assurance scheme. For details of our licensed contractors, contact our customer service team or enquire via our website at www.flowcreteasia.com

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Important Note

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages.

Further Information

To ensure you are specifying a fit-for-purpose floor, please consult our Technical Advisors or visit our website to register your interest in specifying one of the most durable floors on the market.

1. Light colours may require additional coats to achieve desired results 2. It is recommended that top coat colours are close to base coats colours to achieve desired results
3. This product is not UV stable and may discolour unless otherwise stated 4. System Data Sheet to be read in conjunction with Method Statement and Product data Sheets.