

## Deckshield LBD

Deckshield LBD is a polyurethane traffic coating system that incorporates a technically advanced polyurethane based dissipating moisture barrier.

Ensures the controlled dissipation of moisture vapour at the lowest basement car park levels.



### Moisture Barrier:

Tolerates up to 100% relative humidity in the concrete or screed substrate.



### Attractive:

Brightens up dull, dark, musty car parks and suspended floors.



### Hard-Wearing:

Hard-wearing & abrasion resistant suitable for regular vehicle traffic.



### Slip Resistant:

Highly textured finish to provide a safe environment for vehicular ramp users.



### Chemical Resistant:

Excellent resistance to engine oil, battery acid, hydraulic fluid, fuel, etc.



## Technical Profile\*

|  |   |              |              |
|--|---|--------------|--------------|
| <b>FIRE RESISTANCE</b>   |   |              |              |
| EN 13501-1   | B <sub>0</sub> - s1   |              |              |
| <b>SLIP RESISTANCE**</b>   |   |              |              |
| Method described in BS 7976-2 (typical values for 4-S rubber slider)   | Dry >40, Wet depends on specification (in accordance with HSE and UKSRG guidelines) |              |              |
| <b>THERMAL RESISTANCE</b>  |   |              |              |
| Softens over 70°C, Hardens on cooling  |   |              |              |
| <b>CHEMICAL RESISTANCE</b>   |   |              |              |
| Contact Technical Department. Resistant to petrol, diesel, antifreeze, hydraulic fluid, chlorides and battery acids. |   |              |              |
| <b>ABRASION RESISTANCE</b>   |   |              |              |
| ASTM D4060 (1 kg load using CS17 wheels)   | 0.1g loss per 1000 cycles   |              |              |
| <b>WATER PERMEABILITY</b>  |   |              |              |
| Nil - Karsten test (impermeable)   |   |              |              |
| <b>BOND STRENGTH</b>   |   |              |              |
| Greater than cohesive strength of 25 N/mm <sup>2</sup> concrete. > 1.5 MPa   |   |              |              |
| <b>UV LIGHT RESISTANCE (WITH DECKSHIELD UV WB TOPCOAT)</b>   |   |              |              |
| Excellent (non-yellowing)  |   |              |              |
| <b>SPEED OF CURE</b>   | <b>10 °C</b>  | <b>20 °C</b> | <b>30 °C</b> |
| Light Traffic  | 30 h  | 18 h         | 12 h         |
| Full Traffic   | 48 h  | 36 h         | 24 h         |
| Full Chemical Cure   | 12 d  | 7 d          | 6 d          |

\* These figures are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.

\*\*The slipperiness of flooring materials can change significantly, due to the installation process, after short periods of use, due to inappropriate maintenance, longer-term wear and/or surface contaminants (wet or dry). Textured systems are recommended to meet slip resistance value requirements for wet conditions and/or surface contaminants (wet or dry) - please contact our Technical Advisors for further details and specifications.


For a full colour chart and samples, contact your local Flowcrete office.

## Model Specification

|                     |                            |
|---------------------|----------------------------|
| <b>System</b>       | Deckshield LBD             |
| <b>Finish</b>       | Textured                   |
| <b>Thickness</b>    | Dependant on specification |
| <b>Manufacturer</b> | Flowcrete Asia             |

Preparatory work and application in accordance with manufacturer's instructions.

## System Design



## Products Included In This System

|                       |                            |
|-----------------------|----------------------------|
| <b>Primer</b>         | Deckshield DPM             |
| <b>Sand Scatter</b>   | Deckshield Quartz or Oxide |
| <b>Basecoat</b>       | Deckshield Finish          |
| <b>Finishing Coat</b> | Deckshield UV (WB)         |

Detailed application instructions are available upon request.

## Substrate Requirements

Concrete or screed substrate should be a minimum of 25 N/mm<sup>2</sup>, free from laitance, dust and other contamination. The substrate should be free from continuous rising moisture with high hydrostatic pressure.

## Installation Service

The installation should be carried out by a licensed contractor with a documented quality assurance scheme. For details of our licensed contractors, contact our customer service team or enquire via our website at [www.flowcreteasia.com](http://www.flowcreteasia.com)

## Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

## Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

## Important Note

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages.

## Further Information

To ensure you are specifying a fit-for-purpose floor, please consult our Technical Advisors or visit our website to register your interest in specifying one of the most durable floors on the market.

1. Light colours may require additional coats to achieve desired results 2. It is recommended that top coat colours are close to base coats colours to achieve desired results  
3. This product is not UV stable and may discolour unless otherwise stated 4. System Data Sheet to be read in conjunction with Method Statement and Product data Sheets.