



## RUSTIK

- A range of decorative, joint-free stone carpets that bring the vibrancy of the outdoors inside.

## Rustik Range Technical Profile

---



Rustik, Flowcrete Asia's range of decorative stone carpet systems, delivers a wide range of natural and contemporary tones to suit both indoor and outdoor environments.

Whether in a retail or office environment, leisure complex or showroom, Rustik won't fail to impress. Boasting slip and chemical resistance, as well as superior durability, Rustik transforms dull commercial environments whilst delivering a floor finish that withstands cleaning products and chemical attack, provides a safe finish underfoot and stands the test of time.

Rustik can be installed in a variety of patterns using brass or aluminium trims, which are laid on the surface of the floor in a matrix that designates each area of the design. Rustik is then simply used to fill each shape, using contrasting colours to create a truly unique and personalised design.

What's more, the Rustik range benefits from a speedy installation process, reducing impact on trade in commercial businesses, where keeping downtime to a minimum is crucial.

---

## Application Suitability



Retail Outlets



Car Showrooms



Walkways & Paths




Residential



Offices & Lobbies



Hotels & Resorts





# Rustik

Rustik comes in a variety of colourful natural stones encapsulated in a clear epoxy resin, resulting in attractive indoor anti-slip flooring.

Rustik cosmetically enhances, reduces noise, and is easy to clean whilst being highly resistant to chemicals, making it suitable for a limitless list of indoor environments from showrooms and shopping centres to spas, offices and more.



## Attractive:

Decorative finish to transform dull commercial environments.



## Resistant:

Excellent resistance to chemicals, as well as slips and trips.



## Solvent Free & Low Odour:

Improved air quality during installation and beyond.



## Reduces Noise:

Minimises unwanted noise from footsteps in busy commercial spaces.



## Versatile:

Rustik can be applied vertically to walls.

## Colours



Burnt Amber



Jasper



Grey Moonstone



White Sapphire



Black Sapphire



Smokey Quartz

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

## Technical Profile

### APPLICATION SUITABILITY

✓ New Build

✓ Refurbishment

### SLIP RESISTANCE

Method described in BS 7976-2 (typical values for 4-S rubber slider)

Dry > 40, Wet depends on specification (in accordance with HSE and UKSRG guidelines)

### FIRE RESISTANCE

SITAC

Class G  
Certificate No 1721/75

### TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

### ABRASION RESISTANCE

BS8204:Part 2:2002

Class AR2 – Medium duty industrial and commercial

### CHEMICAL RESISTANCE

Contact Technical Department

### BOND STRENGTH

Greater than cohesive strength of 25 N/mm<sup>2</sup> concrete > 1.5 MPa\*

### COMPRESSIVE STRENGTH

BS6319

> 30 N/mm<sup>2</sup>


### FLEXURAL STRENGTH

BS6319

10 N/mm<sup>2</sup>

### SPEED OF CURE\*\*

	10°C	20°C	30°C
Light Traffic	36 hrs	24 hrs	16 hrs
Full Traffic	72 hrs	48 hrs	36 hrs
Full Chemical Cure	12 days	7 days	6 days



\*Assumes concrete compressive strength is greater than 25N/mm<sup>2</sup>

\*\* Cure times at temperatures between 0-30°C can be achieved by altering the quantity of catalyst used. For applications falling outside of this temperature range, please contact your local Flowcrete Technical Department.

# Rustik UV

Rustik UV contains colourful natural stones, encapsulated in a aliphatic, UV stable polyurethane resin, providing attractive reliable outdoor flooring.

Designed to be a flexible solution for areas with heavy traffic, Rustik UV is weather resistant and offers a durable alternative to loose pebbles, whilst maintaining the natural beauty of the outdoors.



## Attractive:

Decorative finish to transform dull commercial environments.



## Resistant:

Excellent resistance to chemicals, and general wear and tear.



## Solvent Free & Low Odour:

Improved air quality during installation and beyond.



## Reduces Noise:

Minimises unwanted noise from footsteps in busy commercial spaces.



## UV Stable:

100% UV light stable. Prevents from yellowing effect.

## Colours



Burnt Amber



Jasper



Grey Moonstone



White Sapphire



Black Sapphire



Smokey Quartz

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

## Technical Profile

### APPLICATION SUITABILITY

✓ New Build	✓ Refurbishment
-------------	-----------------

### SLIP RESISTANCE

Method described in BS 7976-2 (typical values for 4-S rubber slider)	Dry > 40, Wet depends on specification (in accordance with HSE and UKSRG guidelines)
--	--

### TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 65°C

### CHEMICAL RESISTANCE

Contact Technical Department


### BOND STRENGTH

Greater than cohesive strength of 25 N/mm<sup>2</sup> concrete > 1.5 MPa\*

### COMPRESSIVE STRENGTH

BS6319	> 30 N/mm <sup>2</sup>
--------	------------------------

SPEED OF CURE**	10 °C	20 °C	30 °C
Light Traffic	36 hrs	24 hrs	16 hrs
Full Traffic	72 hrs	48 hrs	36 hrs
Full Chemical Cure	12 days	7 days	6 days



\*Assumes concrete compressive strength is greater than 25N/mm<sup>2</sup>

\*\* Cure times at temperatures between 0-30 °C can be achieved by altering the quantity of catalyst used. For applications falling outside of this temperature range, please contact your local Flowcrete Technical Department.





## Flowcrete

World leader in seamless resin flooring solutions and other specialist coatings.

### Africa

South Africa	+27 31 701 0017	southafrica@flowcrete.com
--------------	-----------------	---------------------------

### Asia Pacific (APAC)

Australia	+61 7 3205 7115	australia@flowcrete.com
Bangladesh	+603 6277 9575	bangladesh@flowcrete.com
Hong Kong	+852 2795 0478	hongkong@flowcrete.com
Indonesia	+62 21 252 3201	indonesia@flowcrete.com
Korea	+60 3 6277 9575	korea@flowcrete.com
Malaysia	+60 3 6277 9575	asia@flowcrete.com
New Zealand	+64 7 541 1221	newzealand@flowcrete.com
Pakistan	+60 3 6277 9575	pakistan@flowcrete.com
Philippines	+63 2 834 6506	philippines@flowcrete.com
Singapore	+65 6848 7166	singapore@flowcrete.com
Taiwan	+60 3 6277 9575	taiwan@flowcrete.com
Thailand	+66 2539 3424	thailand@flowcrete.com
Vietnam	+84 28 6287 0846	vietnam@flowcrete.com

## Europe & Middle East (EME)

Bulgaria	+359 898 61 58 31	bulgaria@flowcrete.com
Denmark	+46 435 40 01 10	denmark@flowcrete.com
France	+33 1 60 61 74 42	france@flowcrete.com
Italy	+39 339 4853258	italy@flowcrete.com
Norway	+47 6486 0830	norway@flowcrete.com
Poland	+48 22 879 8907	poland@flowcrete.com
Romania	+40 766 596 991	romania@flowcrete.com
Russia	+7 916 931 3513	russia@flowcrete.com
Spain	+34 937 07 0872	spain@flowcrete.com
Sweden	+46 435 40 01 10	sweden@flowcrete.com
Turkey	+90 212 2946570	turkey@flowcrete.com
UAE	+971 4 347 0460	uae@flowcrete.com
UK	+44 (0) 1270 753 000	uk@flowcrete.com

### India

India	+91 44 40176600	india@flowcrete.com
-------	-----------------	---------------------

## North America

Canada	+1 877-210-2444	canada@flowcrete.com
Mexico	+55 44 40 94 00	mexico@flowcrete.com
USA	+1 513-943-4225	americas@flowcrete.com