

► Floor and wall systems that meet strict hygiene and safety standards for...

## PHARMACEUTICAL ENVIRONMENTS

# Welcome to Flowcrete Asia

---

A critical consideration in the design and construction of pharmaceutical facilities is the flooring used to protect the different operational areas found within. Pharmaceutical brands require floor and wall systems that meet strict hygiene and safety protocols of Good Manufacturing Practice (GMP).

Whether found in production suites, assembly lines or research and development laboratories, flooring materials must offer a wealth of performance characteristics including excellent abrasion, chemical and impact resistance, the ability to withstand extreme temperature swings and provide an easily cleaned, smooth and hygienic finish.

Flowcrete Asia offers a complete package of specialty epoxy, polyurethane, MMA and vinyl ester resin floor and wall systems designed to cater for all areas within pharmaceutical facilities. Some epoxy floor and wall coatings are available that have been qualified as CSM\* for their suitability within cleanroom environments. This is due to their low emissions of airborne particles, low outgassing behaviour and good biological resistance.

*\*CSM (Cleanroom Suitable Materials) is an industry alliance and is a critical qualification for decision-makers selecting materials and equipment in front-end semiconductor manufacturing but also pharmaceutical cleanrooms.*



---

## Application Suitability



Production  
Plants



Assembly  
Lines



Laboratory  
Environments



Chemical  
Storage Areas



Packaging  
& Warehousing



Corridors  
& Stairwells



Maintenance  
& Storage



Gowning Rooms  
& Airlocks



Administrative  
Areas & Rest Rooms



Cleanrooms

Flowcrete's Flowfresh materials contain Polygiene®, a silver ion antimicrobial additive designed to offer enhanced hygiene underfoot.

## Polygiene® Antimicrobial Effectiveness

SARS-CoV	✓
Salmonella Typhi	✓
MRSA	✓
Enterococcus Faecalis	✓
E-coli	✓
Staphylococcus Aureus	✓
Listeria	✓
Streptococcus Pyogenes	✓
C.difficile	✓
Pseudomonas Aeruginosa	✓
Proteus Vulgaris	✓
Campila Bacta	✓




## GMP Compliant Epoxy, Polyurethane & MMA Flooring

Pharmaceutical production facilities require smooth floors, walls and ceilings, free from cracks and open joints that reduce the risk of contamination or bacteria build-up while at the same time ensure a safe, non-slip profile underfoot. Some governing bodies state that the internal surfaces should permit an easy and effective cleaning and, if necessary, disinfection.

Resin flooring systems, including epoxy, polyurethane and MMA systems, ensure a non-porous, smooth and seamless surface where there is nowhere for bacteria or mould spores to grow and are appropriate for GMP installations.

Flowcrete Asia's HACCP International certified and ISO 22196 compliant polyurethane floor screed materials offer enhanced protection with the inclusion of Polygiene®, a silver-ion antimicrobial agent, designed to protect the surface from degradation caused by microbial growth.

### How Does Polygiene® Work?



- 1 The silver ions are distributed throughout the floor.
- 2 The silver ions migrate to the surface.
- 3 They inhibit bacteria growth by penetrating the cell membrane.

## Flowseal EPW Wall (0.2 mm)

A pigmented, water-based, easy-to-clean epoxy wall sealer that is compliant to Cleanroom Suitable Materials requirements.

 **CLEANROOMS**



**Solvent free; low odour**



**Bright, attractive colours available**



**Hygienic and easy to clean**



**Cleanroom Suitable Material (IPA)**



### TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

### VAPOUR PERMEABILITY

ASTM:E96:90

20 g / m<sup>2</sup> / mm / 24 hr

### FIRE RESISTANCE

EN 13501-1

B<sub>FL</sub>-s1



Flowseal EPW Wall is qualified as CSM by the Fraunhofer IPA Institute.  
Please contact your local Flowcrete representative for further information.  
A full technical profile is available at [www.flowcreteasia.com](http://www.flowcreteasia.com)



## Flowshield SL (2–3 mm)

A glossy, self-smoothing floor system that delivers a hard-wearing finish for use in areas that require an easy to clean, seamless finish that can withstand foot, trolley and even rubber wheeled forklift traffic.

 **APPLICATION SUITABILITY AREA**



**Hygienic and easy to clean**



**Hard-wearing and abrasion resistant**



**High chemical resistance**



**Cleanroom Suitable Material (IPA)**

### TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

### SLIP RESISTANCE

Method described in  
BS 7976-2 (Typical values  
for 4-S rubber slider)

Dry > 40, Wet depends on  
specification (In accordance  
with HSE and UKSRG  
guidelines)

### COMPRESSIVE STRENGTH

EN 13892-2

> 50 N/mm<sup>2</sup>




Flowshield SL is qualified as CSM by the Fraunhofer IPA Institute.  
Please contact your local Flowcrete representative for further information.  
A full technical profile is available at [www.flowcreteasia.com](http://www.flowcreteasia.com)


Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.




## Flowseal EPW Wall Colours




Dolphin Grey




Oyster



Pale Green



Silver Grey



Sky Blue



White

## Flowshield SL Colours




Charcoal




Chilli Red




Dark Green



Ivory




Light Green



Light Grey



Mid Blue



Steel Blue



Steel Grey



Yellow

The applied colours may differ from the examples shown.  
For a full colour chart and samples, contact your local  
Flowcrete office.

## Flowseal EPW Wall and Flowshield SL Cleanroom Suitability





# Flowcoat SF41

(Dependent on specification)

A solvent free epoxy resin coating that can deliver an anti-slip profile and protect sustained vehicle traffic, as well as chemical and abrasion resistant.

☒ CHEMICAL, EQUIPMENT STORAGE & WAREHOUSES

## Standard Colours



TEMPERATURE RESISTANCE	
Tolerant of sustained temperatures up to 60°C	
SLIP RESISTANCE	
Method described in BS 7976-2 (Typical values for 4-S rubber slider)	Dry>40, Wet depends on specification (In accordance with HSE and UKSRG guidelines)
FIRE RESISTANCE	
EN 13501-1	B <sub>FL</sub> -s1

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.

# Flowshield Quartz (2–3 mm)

A decorative, hard wearing, self smoothing “liquid-vinyl” epoxy resin flooring system that is suitable for dry, light industrial, commercial and institutional floors requiring a decorative but durable industrial floor performance.

✓ LABORATORIES, GOWNING ROOMS & AIRLOCKS

## Standard Colours



Cream



Light Blue



Pastel Green



Off White



Goosewing Grey



### TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

### SLIP RESISTANCE

Method described in BS 7976-2 (Typical values for 4-S rubber slider)

Dry >40, Wet depends on specification (In accordance with HSE and UKSRG guidelines)

### FIRE RESISTANCE

EN 13501-1

E<sub>FL</sub>-s2

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.



Flowcrete Asia has coatings that are resistant to aggressive chemicals and temperatures up to 165°C







## Flowshield CR (2–3 mm)

A highly chemical resistant, self-smoothing epoxy resin flooring system. Suitable for medium to heavy-duty foot, trolley, pallet truck and rubber wheeled forklift traffic.

✓ LABORATORIES AND CHEMICAL STORAGE

### Standard Colours



Charcoal



Chilli Red




Dark Green



Ivory



Light Green



Light Grey



Mid Blue



Steel Blue



Steel Grey



Yellow



#### TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

#### SLIP RESISTANCE

Method described in BS 7976-2 (Typical values for 4-S rubber slider)

Dry > 40, Wet depends on specification (In accordance with HSE and UKSRG guidelines)

#### FIRE RESISTANCE

EN 13501-1

B<sub>FL</sub>-s1



## Flowshield UCR 1000

An extremely high chemical resistant, hard wearing, attractive, self-smoothing novolac epoxy resin flooring system. Commonly found in dry processing areas.

✓ LABORATORIES, CLEAN ROOMS AND STORAGE AREAS

### Standard Colours



Charcoal



Chilli Red



Dark Green



Ivory



Light Green



Light Grey



Mid Blue



Steel Blue



Steel Grey



Yellow

#### TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

#### SLIP RESISTANCE

Method described in BS 7976-2 (Typical values for 4-S rubber slider)

Dry > 40, Wet depends on specification (In accordance with HSE and UKSRG guidelines)

#### FIRE RESISTANCE

EN 13501-1

B<sub>FL</sub>-s1

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.

## Flowfresh MF (3–4 mm)

A medium duty chemically resistant, antimicrobial treated polyurethane resin finishes. The non-tainting, non-dusting surface provides an easy-to-clean surface with impressive durability under traffic and heavy plant machinery.

☒ PRODUCTION AREAS AND ASSEMBLY LINES

### Standard Colours



#### TEMPERATURE RESISTANCE

From -5°C to 70°C (at 3 mm)  
From -15°C to 90°C (at 4 mm)

#### IMPACT RESISTANCE

EN ISO 6272   15 Nm

#### COEFFICIENT OF THERMAL EXPANSION

ASTM C531    $5.70 \times 10^{-5} \text{°C}^{-1}$

#### ABRASION RESISTANCE

Taber Abrader   0.1 g loss per 1000 cycles  
(1 kg load using CS17 wheels)



## Flowfresh HF & RT (6–9 mm)

Heavy duty, chemical resistant, antimicrobial polyurethane resin floor screeds, providing a durable textured coloured floor finish which incorporates Polygiene® – a performance based antimicrobial which inhibits the growth of bacteria.

☒ CHEMICAL PROCESSING AND HIGH PERFORMANCE AREAS

### Standard Colours



#### TEMPERATURE RESISTANCE

From -25°C to 100°C (at 6 mm)  
From -45°C to 120°C (at 9 mm)

#### IMPACT RESISTANCE

EN ISO 6272   20 Nm

#### COEFFICIENT OF THERMAL EXPANSION

ASTM C531    $3.74 \times 10^{-5} \text{°C}^{-1}$

#### ABRASION RESISTANCE

Taber Abrader   0.12 g loss per 1000 cycles  
(1 kg load using CS17 wheels)





## Performance Benefits

✓	Exceptional chemical resistance*
✓	Shrinkage compensated to reduce stress
✓	Withstands temperatures up to 165°C
✓	Coatings can be applied to a range of substrates
✓	Vertical systems available for tanks and silos
✓	Abrasion and impact resistant
✓	Withstands thermal shock
✓	Anti static grades available to protect against shock
✓	UV resistant
✓	Fast cure systems minimise downtime

\* A detailed chemical resistance chart is available upon request for all Flowchem VE systems. Please contact your local Technical Department for further assistance.

## Flowchem VE

Exposure to concentrated acids, alkalis, aggressive solvents and extreme heat can lead to severe degradation of the floor and wall coverings in any chemical processing environment, as well as metal walkways and structures and tank linings.

Flowcrete's unique shrinkage compensated Flowchem VE range has been engineered to support the toughest of environments, offering first class resistance to most corrosive agents and delivering exceptional protection against their potentially irreparable damage. All systems are fast cure systems, providing a thermal shock resistant finish to ensure a reliable and easily maintained finish.

What's more, with insulation, isolation and electrostatic performance benefits, the Flowchem VE range delivers the ultimate in antistatic corrosion protection to take on the chemical processing industries.

- ✓ Aggressive Production Areas
- ✓ Tank Farms
- ✓ Chemical Processing

- ✓ Primary and Secondary Stage
- ✓ Waste Processing
- ✓ Water Treatment






# Flowtex TQ


A hard wearing, decorative epoxy resin floor topping made up of colour stable quartz granules encapsulated in a clear resin binder. Ideal where the floor is subject to heavy traffic and chemical spills.

☒ WET AND DRY PROCESS AREAS


## Standard Colours




Brown




Dark Grey




Green




Light Blue




Light Grey



Mid Grey



Red



Yellow



### TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 60°C

### ABRASION RESISTANCE

Taber Abrader	50mg loss per 1000 cycles (1 kg load using CS17 wheels)
---------------	--


### FIRE RESISTANCE

BS EN13501-1	C <sub>fi</sub> -s1
--------------	---------------------

### IMPACT RESISTANCE

EN ISO 6272	1 kg weight >1.8m 2 kg weight >1.5m
-------------	--

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.



Flowcrete Asia also manufactures a range of wall coatings and coving mortars to provide a hygienic transition between the floor and wall.




# Flowflake Terroso

A fast-cure, decorative floor coating system, available in a range of attractive colour combinations, Flowflake Terroso contains varying sizes of flakes scattered over a pigmented epoxy base coat and is finished with a tough resistant clear sealer.

☒ PUBLIC AREAS, RESTAURANTS AND HOSPITALS

## Standard Colours



TEMPERATURE RESISTANCE	
Tolerant of sustained temperatures up to 60°C	
SLIP RESISTANCE	
Method described in BS 7976-2 (Typical values for 4-S rubber slider)	Dry>40, Wet depends on specification (In accordance with HSE and UKSRG guidelines)
FIRE RESISTANCE	
EN 13501-1	B <sub>FL</sub> -s1



# Flowflake Kristalina

A decorative, smooth, sparkling epoxy resin floor finish ideal for a modern contemporary environment.


☒ PUBLIC AREAS AND CAFÉS

## Standard Colours



TEMPERATURE RESISTANCE	
Tolerant of sustained temperatures up to 60°C	
SLIP RESISTANCE	
Method described in BS 7976-2 (Typical values for 4-S rubber slider)	Dry>40, Wet depends on specification (In accordance with HSE and UKSRG guidelines)
FIRE RESISTANCE	
EN 13501-1	B <sub>FL</sub> -s1

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.



## Flowcrete

World leader in seamless resin flooring solutions and other specialist coatings.

### Africa

South Africa	+27 31 701 0017	southafrica@flowcrete.com
--------------	-----------------	---------------------------

### Asia Pacific (APAC)

Australia	+61 7 3205 7115	australia@flowcrete.com
Bangladesh	+603 6277 9575	bangladesh@flowcrete.com
Hong Kong	+852 2795 0478	hongkong@flowcrete.com
Indonesia	+62 21 252 3201	indonesia@flowcrete.com
Korea	+60 3 6277 9575	korea@flowcrete.com
Malaysia	+60 3 6277 9575	asia@flowcrete.com
New Zealand	+64 7 541 1221	newzealand@flowcrete.com
Pakistan	+60 3 6277 9575	pakistan@flowcrete.com
Philippines	+63 2 834 6506	philippines@flowcrete.com
Singapore	+65 6848 7166	singapore@flowcrete.com
Taiwan	+60 3 6277 9575	taiwan@flowcrete.com
Thailand	+66 2539 3424	thailand@flowcrete.com
Vietnam	+84 28 6287 0846	vietnam@flowcrete.com

## Europe & Middle East (EME)

Bulgaria	+359 898 61 58 31	bulgaria@flowcrete.com
Denmark	+46 435 40 01 10	denmark@flowcrete.com
France	+33 1 60 61 74 42	france@flowcrete.com
Italy	+39 339 4853258	italy@flowcrete.com
Norway	+47 6486 0830	norway@flowcrete.com
Poland	+48 22 879 8907	poland@flowcrete.com
Romania	+40 766 596 991	romania@flowcrete.com
Russia	+7 916 931 3513	russia@flowcrete.com
Spain	+34 937 07 0872	spain@flowcrete.com
Sweden	+46 435 40 01 10	sweden@flowcrete.com
Turkey	+90 212 2946570	turkey@flowcrete.com
UAE	+971 4 347 0460	uae@flowcrete.com
UK	+44 (0) 1270 753 000	uk@flowcrete.com

### India

India	+91 44 40176600	india@flowcrete.com
-------	-----------------	---------------------

## North America

Canada	+1 877-210-2444	canada@flowcrete.com
Mexico	+55 44 40 94 00	mexico@flowcrete.com
USA	+1 513-943-4225	americas@flowcrete.com